SINGLE-FUNCTION BLACK & WHITE PRINTER OFFERING RELIABILITY AND GREATER COST CONTROL.

The i-SENSYS LBP210 series are fast, double sided, A4 black and white printers engineered to enhance work flow and productivity, and cut costs. Delivering improved, high-quality results, they are ideal for SMEs.







LBP212dw

LBP214dw

LBP215x

- Save time with fast print speeds of up to 38ppm (LBP214dw/LBP215x)
- High quality 1200 x 1200 dpi print resolution
- Easy operation with large colour touchscreen on LBP215x
- Compatible with AirPrint and Mopria for mobile connectivity
- Large storage with 1GB internal memory
- Secure PIN printing from mobile devices (LBP214dw/ LBP215x)
- Improved flexibility with varied media support; A4, A5, A6
- Quick and simple mobile connectivity via QR code (LBP215x)
- Application Library allowing automation, added shortcuts and a customised interface(LBP215x)
- Universal Login Manager function and uniFLOW ready (LBP215x)



i-SENSYS LBP212dw \ LBP214dw \ LBP215x

OPTIONAL ACCESSORIES

Cassette Feeding Module AH1

• Additional 550 sheet paper cassette, 1unit can be added to main unit

Barcode Print Kit- E1E (Available on LBP215x)

• Installs bar code fonts for bar code printing. This kit, which is delivered electronically, includes a license access certificate for activation.

LBP215x: 438 mm x 373 mm x 312 mm LBP214dw/LBP212dw: 401 mm x 373 mm x 250 mm

LBP215x: 12.7 cm LCD Colour Touch Screen LBP214dw/LBP212dw: 5 Line LCD, 3 LED (Job, Error, Energy saver), Buttons, 10-key numeric keypad

LBP215x/LBP214dw: UFRII, PCL 5e4, PCL6, Adobe®

LBP215x: 93 PCL fonts, 136 PS fonts LBP214dw/LBP212dw: 45 PCL fonts, 136 PS fonts

USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection

Wireless 802.1lb/g/n, Wireless Direct Connection
Remote User Interface (RUI),
Department ID Management,
Toner Status Tool,
IW Management Console: Server-based software for
centralised management of a fleet of devices
eMaintenance: embedded RDS allows remote
eMaintenance services such as meter capture, automatic
consumables management and remote diagnostics.
Universal Log-in Manager (LBP215x only)
uniFLOW online (LBP215x only)
uniFLOW online Express (LBP215x only)
uniFLOW compatibility with embedded uniFLOW Login
Device Client (LBP215x only)

Medawer BJ / Windows** RJ / Server** 2016

Windows* 10 / Windows* 8.1 / Windows* 7 / Server* 2016 / Server* 2012R2 / Server* 2012 / Server* 2008R2 / Server*

Cassette Feeding Module-AHI
MICArd Multi (Card reader for identification with RFID or
magnetic cards with uniFLOW) (LBP215x only)
Micard Plus (Card reader for identification with RFID or
magnetic cards with uniFLOW) (LBP215x only)
MiCard Attachment kit-BI (LBP215x only)
Barcode Printing Kit-EIE (LBP215x only)

LBP215x: Approx. 9.9 Kg LBP214dw/LBP212dw: Approx. 9.5 Kg

PostScript LBP212dw: UFRII, PCL 5e4, PCL6

Mac OS X version 10.8.5 & up

Cartridge 052 (3,100 pages ⁶)⁷ Cartridge 052H (9,200 pages ⁶)⁷

800MHz x 2

1GB

Serve 2008

Linux

Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation)

TECHNICAL SPECIFICATIONS

PRINTER ENGINE

Print speed

Printing method Up to 1200 x 1200 dpi Print quality Print resolution 600 x 600 dpi

Warm-up time First Page Out Time Approx: 5.5 seconds or less

Recommended Monthly Print Volume

Duty cycle Print margins

Advanced printing features

MEDIA HANDLING Paper input (Standard)

Paper input (Option) Paper output Media types

Media sizes

Media weights

Double sided printing

GENERAL FEATURES Power requirements

Noise level

LBP214dw, LBP215x Single sided: Up to 38 ppm (A4) Up to 63.1 ppm(A5-Landscape) Double sided: Up to 30.3 ipm (A4) LBP212dw Single sided: Up to 33 ppm (A4)

Up to 52.5 ppm(A5-Landscape) Double sided : Up to 26.4 ipm (A4)

750 - 4,000 pages per month

Secure Print (LBP214dw, LBP215x only)
Print from USB memory key (JPPG/TIFF/PDF)
Barcode Print ¹ (LBP215x only)
Google Cloud Print Ready
iOS: AirPrint, Canon PRINT Business app
Android: Mopria certified, Canon Print Service Plug-in,
Canon PRINT Business app

250-sheet cassette 100-sheet multi-purpose tray

550-sheet cassette

150-sheet

Plain paper, Recycled paper, Heavy Paper, Thin paper,

Cassette (standard and optional): 52 to 120 g/m 2 multi-purpose tray: 52 to 163 g/m 2

220-240V(±10%) 50/60Hz (±2Hz)

220-240V(£10%) \$0/60Hz (£2Hz)
Maximum: Approx. 1300 W
Standby: Approx. 1300 W
Sleep mode: Approx. 0.9 W
Typical Electricity Consumption (TEC):
LBP215x/214dw 1.2 kWh/week (230V)
LBP212dw 1.1 kWh/week (230V)
For detailed information relating to Lot26 regulation,
please go to:
http://www.canon-europe.com/For_Work/Lot26/index.aspx

Sound Pressure²: Active: 56 dB Standby: Inaudible³ Sound Power²: Active: 72.2 dB Standby: Inaudible³ Dimensions (W x D x H)

Operating environment

Weight

Control panel

CONTROLLER

Memory

Fonts

Processor Speed

Printer Languages

Operating Systems

Compatibility

CONSUMABLES

All-in-One cartridges

ACCESSORIES/ OPTIONS

Interface and connectivity

Monochrome laser beam printing

Approx. 14 seconds or less from power on

80 000 pages

5 mm-top, bottom, left and right Secure Print (LBP214dw, LBP215x only)

Label, Post card, Envelope

Cassette (Standard and optional):
A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive,
Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL,
Foolscap, 16K, Custom sizes: Min. 105 x 148 mm
Max. 215.9 x 355.6 mm.

Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Indexcard, Envelope (COM10, Monarch, C5, DL), Custom sizes: Min 76.2 x 127 mm Max. 215.9 x 355.6 mm.

A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, GLGL, Foolscap Custom size - Min. 210 x 279 4 mm May 215 0 755 6

Foolscap Custom size - Min. 210 x 279.4 mm Max. 215.9 x 355.6 mm 60 to 120 $\rm g/m^2$

(1) Accessory - Barcode Printing Kit-E1E - is required ^[2]Declared noise emission in accordance with ISO 9296

 $^{[3]}$ lnaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779

[4] A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device.

^[5]Web distribution only Available from December 2018

[6]Based on ISO/IEC 19752

[7]Printer ships with starter cartridge (Black: 1,600pages)

Canon Inc. canon.com

Canon Europe canon-europe.com

English edition

© Canon Europa N.V.,2018



SINGLE-FUNCTION BLACK & WHITE PRINTER OFFERING RELIABILITY AND GREATER COST CONTROL.

The i-SENSYS LBP210 series are fast, double sided, A4 black and white printers engineered to enhance work flow and productivity, and cut costs. Delivering improved, high-quality results, they are ideal for SMEs.

Sales Start Date: April 2018

i-SENSYS LBP212dw \ LBP214dw \ LBP215x



PRODUCT DETAILS:

Product name	Mercury code	EAN Code
i-SENSYS LBP212dw	2221C006AA	4549292090208
i-SENSYS LBP214dw	2221C005AA	4549292090192
i-SENSYS LBP215x	2221C004AA	4549292090185

ACCESSORIES:

Product name	Mercury code	EAN Code
Cassette Feeding Module-AH1	0732A033AA	4549292092769
MiCard Attachment kit-B1	5146B002AA	4549292027235
Barcode Printing Kit-E1E	5143B002AA	N/A (e-delivery)

CONSUMABLES:

Product name	Mercury code	EAN Code
Cartridge 052	2199C002AA	4549292089400
Cartridge 052 H	2200C002AA	4549292089424

EASY SERVICE PLAN:

Product Name	Mercury Code	EAN Code
Installation service	7950A546AA	4960999794426
3-year on-site next day service-Pack A (LBP212dw & LBP214dw)	7950A525AA	4960999793290
3-year on-site next day service-Pack B (LBP215x)	7950A526AA	4960999793306

